

UC SERIES PD-C360i/8 mini UC

ESYLUX



Order description	Item number	GTIN
PD-C360i/8 mini UC opal matt	EP10427343	4015120427343



Short description

- Presence detector with 360° field of detection for recessed ceiling mounting
- range of up to 8 m in diameter for use in connection with building management systems
- Operating voltage 12-36 V DC or AC voltage (AC/DC)
- Potential-free software-controlled switching output (C/O)
- Connectable and disconnectable display of detection
- Silent switch up to the maximum of 2 A

Technical data

Installation type	Recessed ceiling mounting
Channel 1	Lighting
Interface	switching/dimming
dimensions	, Ø 33 mm
Contact	make contact/floating
Installation dimension	Installation depth 45 mm, Ø 25 mm
Light measurement	mixed light
Light value	approx. 5 - 2,000 lux
Switching delay from "light to dark" [s]	30 s
Switching delay from "dark to light" [s]	300 s
Weight	0.068 kg
Mains voltage	12-36 V UC (~/=)
Field of detection	360°
Range	approx. 8 m in Ø, at an installation height of 3 m to 5 m
Zal. installation height	3 m
Slave input	No
Switching capacity channel 1	12 - 36 V UC (AC/DC), 2 A
Switch input	yes
Switch-off delay time	impulse/approx. 1 minute – 60 minutes
Analogue output	0 - 10 V DC
Protection type	IP 55
Protection class	III
Permissible ambient temperature	0 °C...+50 °C
Housing material	UV-stabilised PE, UV-stabilised polycarbonate
Conformity	CE, RoHS
Setting options	electronically by infrared Mobil-PDi DUO/MDi remote control (order separately)
Relative humidity	5 - 93 %, non-condensing
Supply line	60 cm, 4 x 1.00 mm²
Included in delivery	includes lens mask, spring installation clips, clamping installation ring

Accessories

- EM10425509 - Mobil-PDi/MDi silver/metallic blue
- EP10426391 - Spotlight adapter 51/25 opal frosted
- EP10433993 - Mobil-PDi/MDi-universal white

Note: Order remote control separately.

28-10-2017

www.esylux.com

UC SERIES PD-C360i/8 mini UC

ESYLUX

Order description	Item number	GTIN
PD-C360i/8 mini UC opal matt	EP10427343	4015120427343



Dimensions in mm

