

Dimensioner_NKO

Model Q_{nom}/V_{tank}	Q_{nom} (dm³/s) (NS)	tank diameter dn, mm	Hw / height supply, mm	Min. depth, mm (A mått)	in/out pipe dn	Sedimentation capacity, dm³	Oil storage capacity, dm³	weight, kg
NKO 1,5/150	1,5	1000	580	570	160	150	180	2450
NKO 1,5/300	1,5	1000	790	610	160	300	180	2450
NKO 3/300	3	1000	790	610	160	300	180	2450
NKO 3/600	3	1000	1170	480	160	600	180	2450
NKO 3/600	3	1200	940	660	160	600	260	4800
NKO 3/2500	3	2000	1200	450	160	2500	760	7300
NKO 6/600	6	1200	940	660	160	600	260	3400
NKO 6/1200	6	1500	1080	570	160	1200	420	4950
NKO 6/2500	6	2000	1200	450	160	2500	760	7300
NKO 6/5000	6	2500	1420	430	160	5000	1200	12000
NKO 10/1000	10	1500	970	680	160	1000	420	4950
NKO 10/2000	10	2000	1040	410	160	2000	760	7300
NKO 10/5000	10	2500	1420	430	160	5000	1200	12000
NKO 15/1500 (1500)	15	1500	1430	720	200	1500	780	6200
NKO 15/1500 (2000)	15	2000	1060	490	200	1500	1410	7300
NKO 15/3000	15	2000	1540	510	200	3000	1410	7300
NKO 20/2000	20	2000	1220	530	200	2000	1410	7300
NKO 20/4000	20	2500	1400	550	200	4000	2220	12000
NKO 30/3000	30	2000	1620	630	315	3000	1800	7300
NKO 30/6000 B	30	2500	1890	660	315	6000	2900	13000
NKO 40/4000	40	2500	1480	670	315	4000	2900	12000
NKO 40/8000 B	40	3000	1800	650	315	8000	4800	
NKO 50/5000 B	50	3000	1930	620	315	5000	4590	