



Jets™ VFD valve is a vacuum operated flush and discharge valve.

Features:

- Low water consumption.
- Design optimized for easy maintenance.
- Ideal for retrofit of existing installations.

IMPORTANT! Note: for deliveries to Australia and New Zealand the product delivery DOES NOT include the 035504000 Ball valve DN15. Please refer to Australian/New Zealand standards and contact your local plumber regarding approved installation methods.

Technical Data




Type	Vacuum Operated
Outside Dimensions.....	240 x 200 x 310 mm (LxWxH)
Discharge Valve Outlet.....	Outside diameter Ø 50 mm
Generic Material.....	POM
Water Connection.....	½" male BSP
Net Weight.....	1.895 kg

Operating Data

Flushing Time.....	5 seconds
Discharge Time.....	2 seconds
Water Pressure.....	2-7 bar
Operating Vacuum.....	Recommended 30-55 % Vacuum
Air Consumption.....	Approx. 48 liters at 50% Vacuum
Water Consumption.....	1L (3 bar)
Temperature Range.....	Minimum 1°C to Maximum 60°C (unless frost protection measures are taken)

Disclaimer

Note: Our products and services are offered and sold subject to Jets Vacuum AS' General Sales Conditions, copies of which will be furnished upon request. Information provided herein is solely for information purposes, does not constitute any warranty or representation of any kind and is subject to change without notice. We strive to reproduce product colors reasonably accurate. Without prior written approval, this document or any part of may not be reproduced in any form. Jets™, Vacuumarator™, Helivac™, VC™, VOD™, CVS™ and Softsound™ are trademarks and/or registered trademarks of Jets. © Jets AS. All rights reserved.






Components

1 Hose	034509000*
■ (1 of 034509000 = 1m in length)	
2 D Valve, Piston	050513025*
3 Screw, M5x10	036531600*
4 Hose w/ball valve 550mm	034509620*
5 Bracket BR3	054110032*
6 Gasket	037504200*
7 Distributor w/NR Valve	101100116*
8 Hose	034509010*
■ (1 of 034509010 = 1m in length)	
9 VPC-V Controller	101100010*

* Component/s available as replacement parts.

Dimension Drawings



A.....240mm

B.....200mm

C.....310mm

D.....50mm

E.....Ø60